The Pursuit of Excellence


Automated **VHP Generator** for bio decontamination



- · Runs on compressed air.
- Generates dry disinfection vapour of H2O2 based disinfectants.
- · Gas like diffusion and uniform exposure.
- Enhances standard bio cleaning process



3 Nozzle vaporization output ensures 360° treatment



EASY TO HANDLE

Plug-and-play mobile unit.

Touch screen HMI for easy start-up and device set-up.

SECURED PROCESS

Digital registration of different variables that will ensure cycle has been properly performed.

Digitally controlled dispensing & disinfection process cycle. Reproducible results

FEATURES

- · Equipped with Digital Pressure Switch
- Ultra low consumption: 200ml/1000 ft³ 7ml/m³
- Treatment volume of space up to 1000m³/35000 ft³
- Micro biologically validated process ensures Effective destruction of pathogens & multi resistant microorganisms.
- Complies with aseptic area & sterile area norms for airborne disinfection process as well as device.
- · Absolutely safe for use in presence of OT/medical equipment.



DATA TRACEABILITY

Process data traceable, retrievable with USB drive. Can retrieve the following information for each process:

- Treatment Date & Time
- · User name, Room Name, Room volume
- Disinfectant Name, Total Consumption of
- Disinfectant in ml, Treatment duration
- · Application dosage



DIGITAL USER INTERFACE FOR AUTOMATED PROCESS

- Enter room size & set the volume of room under the treatment.
- Pour required solution advised by the machine.
- Delayed start to leave the premises & Auto OFF operations.

CAN SAVE UPTO 20 DIFFERENT ROOM SIZES.


MATERIALS & SPECIFICATIONS

- Requires 40CFM of compressed air @ 87 PSI (6 bar)
- · All stainless steel unit
- · Tank Capacity: 12 litres
- · Easy to refill or replace disinfectant container.
- All key components in SS316 : Nozzle assembly
- · liquid line parts, Solution tank
- · Liquid and air line tubing: Medical grade.
- Power supply: 15amps, 230Vac, 50Hz/60Hz
- Dimensions: 500mm L X 420mm W X 850mm H
- · Empty weight: 30kg
- Continuous duty hr 99 minutes
 *specifications are subject to change

APPLICATIONS

- · Hospitals: Operation Theatres, ICUs
- · Pharmaceutical Mfg. Plants : Sterile areas
- · Laboratories : Microbiology, Tissue Culture
- · Bio decontamination Treatment again Disease Epidemic
- Medical Device Manufacturing
- · Food Processing Plants

INSIGHT INTO USER FRIENDLY, EXTENSIVE PROGRAM




Program Touch Screen




USB drive for data traceability

DD/MM/YY



Different user access rights with password protection



HH:MM:SS

Parameters and save it.

| DD/MM/YY APPLICATION DOSAGE HH:MM:SS | | | | |
|--------------------------------------|-------------|--|--|--|
| 7ml | 9ml | | | |
| CUBIC METER | CUBIC METER | | | |
| 11ml | 14ml | | | |
| CUBIC METER | CUBIC METER | | | |
| BACK | | | | |

Optional application dosages settable In addition to standard dosage

| DD/MM/YY | ROOM SAVING | HH:MM:SS |
|-----------------|-----------------|----------|
| ROOM NO: | 8 | |
| ROOM NAME: | PRODUCTION 2 | |
| LENGTH: | 6.0 MTR. | |
| WIDTH: | 5.0 MTR. | |
| HEIGHT: | 3.5 MTR. | |
| ROOM VOLUME : | 105 m³ | |
| TREATMENT DURAT | ION: 12 MIN. 3: | 3 SEC. |
| ВАСК | | NEXT |


Machine can save up to 20 different room sizes.

| DD/MM/YY | ROOM SELECTION | | | HH:MM:SS |
|-------------|----------------|-------|----------------|----------|
| ROOM NO: | | 5 | | |
| ROOM NAME | : | FILLI | NG AREA | |
| LENGTH: | | 8.0 | MTR. | |
| WIDTH: | | 8.0 | MTR. | |
| HEIGHT: | | 3.0 | MTR. | |
| ROOM VOLUM | ЛE : | 192 | m ³ | |
| DISINFECTAN | IT USED : | 672 | ml. | |
| DM WATER: | | 672 | ml. | |
| ВАСК | | | | NEXT |


User can identify pre saved room with Room no and name.

| DD/MM/YY | USER DATA | | HH:MM:SS |
|----------|-----------|--|----------|
| | NAME | | PASSWORD |
| 01 | CHIRAG | | 1234 |
| 02 | PARTH | | 5678 |
| 03 | RAJESH | | 8282 |
| 04 | RAMESH | | 9595 |
| 05 | ARUN | | 2552 |
| EXIT | | | NEXT |


Offers up to 10 different users password Protected access.




Manager's access rights password protected



Display screen when treatment is in progress.




Enter room size or choose pre saved room for Treatment & machine offers auto calculated process Parameters such as volume of required dilution, Treatment duration to proceed with the cycle.



Saved process data tracing and retrieving Through USB drive.

The format of retrieved process data with detailed information on cycle parameters.



^{*}Above report is for reference, actual report and format may differ.